



select	Inquiry Designation		Principal Dimensions(mm)						Basic Load Ratings(KN)		Limited Speed(rpm)	Weight (kg)
			d	D	B	rs min	rs1min		Dynamic(Cr)	Static(Cor)	Grease Oil	
NU204E	20	47	14	1	0.6	25.7	22.6		15000	18000	0.122	
NU205E	25	52	15	1	0.6	29.3	27.7		13000	15000	0.151	
NU206E	30	62	16	1	0.6	39	37.5		11000	13000	0.226	
NU207E	35	72	17	1.1	0.6	50.5	50		9500	11000	0.327	
NU208	40	80	18	1.1	1.1	43.5	43		9400	11000	0.378	
NU208E	40	80	18	1.1	1.1	55.5	55.5		8500	10000	0.426	
NU209	45	85	19	1.1	1.1	46	47		8400	9900	0.432	
NU209E	45	85	19	1.1	1.1	63	66.5		7600	9000	0.495	
NU210	50	90	20	1.1	1.1	48	51		7600	9000	0.47	
NU210E	50	90	20	1.1	1.1	66	72		6900	8100	0.54	
NU211	55	100	21	1.5	1.1	58	62.5		6900	8200	0.638	
NU211E	55	100	21	1.5	1.1	82.5	93		6300	7400	0.718	
NU212	60	110	22	1.5	1.5	68.5	75		6400	7600	0.818	
NU212E	60	110	22	1.5	1.5	97.5	107		5800	6800	0.923	
NU213	65	120	23	1.5	1.5	84	94.5		5900	7000	1.02	
NU213E	65	120	23	1.5	1.5	108	119		5400	6300	1.21	
NU214	70	125	24	1.5	1.5	83.5	95		5500	6500	1.12	
NU214E	70	125	24	1.5	1.5	119	137		5000	5900	1.3	
NU215	75	130	25	1.5	1.5	96.5	111		5100	6000	1.23	
NU215E	75	130	25	1.5	1.5	130	156		4700	5500	1.41	
NU216	80	140	26	2	2	106	122		4800	5700	1.5	
NU216E	80	140	26	2	2	139	167		4400	5100	1.67	
NU217	85	150	28	2	2	120	140		4500	5300	1.87	
NU217E	85	150	28	2	2	167	199		4100	4800	2.11	

NU200 Series

NU218	90	160	30	2	2	152	178	4300	5000	2.3
NU218E	90	160	30	2	2	182	217	3900	4600	2.44
NU219	95	170	32	2.1	2.1	166	195	4000	4700	2.78
NU219E	95	170	32	2.1	2.1	220	265	3600	4300	3.02
NU220	100	180	34	2.1	2.1	183	217	3800	4500	3.33
NU220E	100	180	34	2.1	2.1	249	305	3500	4100	3.66